

5-17-2012

MATERIAL SAFETY DATA SHEET

PolyBlend Sanded Grout

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: PolyBlend Sanded Grout
Product Use: Sealant.
Manufacturer/Supplier: Custom Building Products
13001 Seal Beach Blvd
Seal Beach, CA 90740
Phone Number: (562) 598-8808
Emergency Phone: INFOTRAC 1-800-535-5053 (US and Canada)
INTERNATIONAL + 1-352-323-3500
Date of Preparation: March 5, 2010

Polyblend Sanded
Grout

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: Irritating to eyes. May cause burns in the presence of moisture.
Skin: May cause skin irritation. May cause burns in the presence of moisture.
Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.
Inhalation: May cause respiratory tract irritation.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.

Medical Conditions Aggravated By Exposure: Because of its irritating properties, dust may aggravate preexisting skin, eye, and respiratory conditions.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Silica, crystalline, quartz	14808-60-7	40 - 70
Portland cement	65997-15-1	15 - 40
Ferric oxide	1309-37-1	1 - 5

MATERIAL SAFETY DATA SHEET

PolyBlend Sanded Grout

Section 4: FIRST AID MEASURES

- Eye Contact:** In case of contact, immediately flush eyes with plenty of water. If easy to do, remove contact lenses, if worn.
- Skin Contact:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Not flammable by WHMIS/OSHA criteria.

Means of Extinction:

Suitable Extinguishing Media: Treat for surrounding material.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental Precautions: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Pick up large pieces, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Clean-Up: Vacuum or sweep material and place in a disposal container.

Other Information: Not available.

Section 7: HANDLING AND STORAGE

Handling:

Avoid contact with skin and eyes. Do not swallow. Good housekeeping is important to prevent accumulation of dust. Avoid generating dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Use only in well-ventilated areas. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

MATERIAL SAFETY DATA SHEET

PolyBlend Sanded Grout

Storage:

Keep out of the reach of children. Store in dust-tight, dry, labeled containers. Keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers. Use corrosion-resistant structural materials and lighting and ventilation systems in the storage area.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Silica, crystalline, quartz Portland cement	((10 mg/m ³)/(%SiO ₂ +2) TWA (resp));	
	((30 mg/m ³)/(%SiO ₂ +2) TWA (total));	
	((250)/(%SiO ₂ +5) mppcf TWA (resp))	0.025 mg/m ³
Ferric oxide	15 mg/m ³ (total); 5 mg/m ³ (resp)	10 mg/m ³ (total)
		5 mg/m ³ (iron oxide fume; dust as Fe)

Engineering Controls: When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Powder.
Color:	Not available.
Odour:	Not available.
Odour Threshold:	Not available.
Physical State:	Solid.
pH:	Not available.
Viscosity:	Not available.
Freezing Point:	Not available.
Boiling Point:	Not available.
Flash Point:	Not available.
Evaporation Rate:	Not available.
Lower Flammability Limit:	Not available.

MATERIAL SAFETY DATA SHEET

PolyBlend Sanded Grout

Upper Flammability Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Specific Gravity:	2.7
Solubility in Water:	Partial.
Coefficient of Water/Oil Distribution:	Not available.
Auto-ignition Temperature:	Not available.
Percent Volatile, wt. %:	Not available.
VOC content, wt. %:	0%, Not applicable; 0 wt, Not applicable.

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Keep dry in storage.

Conditions of Reactivity: Heat. Incompatible materials. Moisture.

Incompatible Materials: Acids. Ammonium salts. Aluminum. Alkalis.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD ₅₀ (oral)	LC ₅₀
Silica, crystalline, quartz	500 mg/kg, rat	Not available.
Portland cement	Not available.	Not available.
Ferric oxide	1000 mg/kg, rat	Not available.

Eye: Irritating to eyes. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Skin: May cause skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Lungs.

Chronic Effects: Hazardous by WHMIS/OSHA criteria.

Carcinogenicity: Hazardous by WHMIS/OSHA criteria.

MATERIAL SAFETY DATA SHEET

PolyBlend Sanded Grout

Ingredient

Silica, crystalline, quartz
Portland cement
Ferric oxide

Chemical Listed as Carcinogen or Potential Carcinogen *

G-A2, I-1, N-1, CP65
Not listed.
Not listed.

* See Section 15 for more information.

Mutagenicity: Not hazardous by WHMIS/OSHA criteria.

Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Not hazardous by WHMIS/OSHA criteria.

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Classification

Not regulated

TDG Classification

Not regulated

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

SARA Title III

Ingredient

Section 302 (EHS) TPQ (lbs.)

Section 304 EHS RQ (lbs.)

CERCLA RQ (lbs.)

Section 313

Silica, crystalline, quartz
Portland cement
Ferric oxide

Not listed.
Not listed.
Not listed.

Not listed.
Not listed.
Not listed.

Not listed.
Not listed.
Not listed.

Not listed.
Not listed.
Not listed.

MATERIAL SAFETY DATA SHEET

PolyBlend Sanded Grout

State Regulations

California Proposition 65:

This product contains a chemical known to the state of California to cause cancer.

Global Inventories

Ingredient

Silica, crystalline, quartz
Portland cement
Ferric oxide

Canada	USA
DSL/NDSL	TSCA
DSL	Yes.
DSL	Yes.
DSL	Yes.

HMIS - Hazardous Materials Identification System

Health - 2*

Flammability - 0

Physical Hazard - 0

PPE - B

NFPA - National Fire Protection Association:

Health - 2

Fire - 0

Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

Class D2A - Carcinogenicity

Class D2A - Chronic Toxic Effects

WHMIS Hazard Symbols:



SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: March 5, 2013

Version #: 1.0

Prepared by: Nexreg Compliance Inc.
Phone: (519) 488-5126
www.nexreg.com