

Sub 616054

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory-Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List) **ENCORE** *Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.*

Section I NA = Not Applicable NTA = No Information Available

Manufacturer's Name: Sunburst Chemicals, Inc. Emergency Telephone Number: 1-866-303-6943 (7 days/24 hours)

Address (Number, Street, City, State, and ZIP Code): 220 W. 86th St. Telephone Number For Information: (952) 884-3144

Bloomington, MN 55420 Date Prepare: 05-26-11

Chemical Family: Alkaline Detergent Signature of Preparer (optional):

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Sodium Metasilicate	2mg/m ³	2mg/m ³		
CAS# 6834-92-0				
Sodium Hydroxide	2 mg/m ³	2 mg/m ³		
CAS# 1310-73-2				

PA: Identification of specific ingredients is being withheld as a trade secret.
NJ-TSRN 6160-5050

Section III - Physical/Chemical Characteristics

Boiling Point	NA	Specific Gravity (H ₂ O= 1)	1.80
Vapor Pressure (mm Hg.)	NA	Melting Point	160° F.
Vapor Density (AIR= 1)	NA	Evaporation Rate (Butyl Acetate = 1)	NA
pH, 1%	11.7	% Volatile, 1%	<20%

Solubility In Water: Completely soluble up to 10% W/W.
Appearance and Odor: Heavy pink solid with white granules, low odor.

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used): None.	Flammable Limits	LEL: NA	UEL: NA
----------------------------------	------------------	---------	---------

Extinguishing Media: Water, CO₂, Dry chemical.
Special Fire Fighting Procedures: No unusual hazards In extreme heat product and container may melt and spill.
Unusual Fire and Explosion Hazards: None.

HMIS		NFPA			
1 HEALTH	HEALTH HAZARD	FIRE HAZARD Flash Points		SPECIFIC HAZARD	REACTIVITY
0 FLAMMABILITY	4 Deadly	4 Below 73° F (Boiling pt. below 100° F)		Oxidizer OX	4 May detonate
0 REACTIVITY	3 Extreme danger	3 Below 73° F (Boiling pt. at/above 100° F) and/or at/above 73° F - not exceeding 100° F		Acid ACID	3 Shock and heat may detonate
B PERSONAL PROTECTION	2 Hazardous	2 Above 100° F, Not Exceeding 200° F		Alkali ALK	2 Violent chemical change
	X 1 Slightly hazardous	1 Above 200° F		Corrosive COR	1 Unstable if heated
	0 Normal material	X 0 Will not burn		Use H ₂ O WATER	X 0 Stable
				Radioactive	

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (Materials to Avoid)
None.

Hazardous Decomposition or Byproducts
None.

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI - Health Hazard Data

Routes(s) of Entry:	Inhalation? NO	Skin? Possible	Ingestion? Possible
---------------------	-------------------	-------------------	------------------------

Health Hazards (Acute and Chronic)
ACUTE - Encore and solutions are corrosive to skin and eyes, can cause poisoning if ingested. CHRONIC - dermatitis.

Carcinogenicity:	NTP? NIA	IARC Monographs? NIA	OSHA Regulated? NIA
------------------	-------------	-------------------------	------------------------

Signs and Symptoms of Exposure
Redness, burning sensation in eyes or skin. Bitter taste, nausea if ingested.

Medical Conditions Generally Aggravated by Exposure

Open sores or wounds.

Emergency and First Aid Procedures

Thoroughly rinse exposed areas for 15 minutes. Get medical attention for eyes.

INTERNAL - drink a large quantity of milk or water. Get immediate medical attention.

Section VII - Precautions for Safe Handling and Use

Absorb spilled material with an absorbent material such as clay, sawdust, or sand. sweep up as much of this as possible and place in a sealed, labeled container or in a proper landfill. Thoroughly rinse the affected area with water.

Waste Disposal Method
Spilled material should be collected as above for disposal in a landfill according to Federal, State, and Local regulations.

Precautions to Be Taking in Handling and Storing
Avoid touching the contents of containers with exposed skin.

Other Precautions
Use caution when changing empty containers to avoid spilling water from inside the container on exposed skin, eyes or clothing. Keep out of reach of children.

Section VIII - Control Measures

Respiratory Protection (Specify Type)
Not required.

Ventilation	Local Exhaust NA	Special NIA
	Mechanical (General) NIA	Other NIA

Protective Gloves Rubber or vinyl recommended.	Eye Protection Safety glasses, goggles recommended.
---	--

Other Protective Clothing or Equipment
Not required.

Work/Hygienic Practices
Always wash hands after handling.